

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method of operating a network entity at an intermediate node between a mobile node in a foreign network and a correspondent node, the method comprising: comprising

allocating a secondary care of address to the network entity; and
sending a packet, addressed to the correspondent node, from the network entity, wherein
the packet has the secondary care of address as a source address.

2. (Previously Presented) The method of claim 1, wherein the packet is a binding update.

3. (Previously Presented) The method of claim 2, further comprising allocating to the mobile node a care-of address within the foreign network, wherein the binding update comprises an indication of the care-of address.

4. (Previously Presented) The method of claim 3, wherein the network entity receives, in a session between the correspondent node and the mobile node, one or more session packets with the correspondent node address as the source address and the care-of address as the destination address, and forwards the session packets to the mobile node.

5. (Previously Presented) The method of claim 4, wherein the session packets are tunnelled from the correspondent node to the network entity and decapsulated prior to being forwarding to the mobile node.

6. (Previously Presented) The method of claim 4, wherein the network entity translates the destination address of the session packets to a home address of the mobile node prior to forwarding the session packets to the mobile node.

7. (Currently Amended) The method of ~~claim 2~~claim 3, wherein the network entity sends, in a session between the mobile node and the correspondent node, one or more session packets in a tunnel from the network entity to the correspondent node, with the care-of address as the source address and the correspondent node address as the destination address.

8. (Previously Presented) The method of claim 7, wherein the tunnelled session packets have a home address of the mobile node as an inner source address.

9. (Previously Presented) The method of claim 1, wherein the packet is a session packet in a session between the mobile node and the correspondent node.

10. (Currently Amended) A method of operating a network entity at an intermediate node between a mobile node in a foreign network and a correspondent node, the method comprising: comprising

allocating a secondary care of address to the network entity; and
receiving from the correspondent node a packet addressed to the secondary care of address to the network entity and having a correspondent node address as the source address.

11. (Previously Presented) The method of claim 10, wherein the packet is a session packet in a session between the correspondent node and the mobile node, and the network entity forwards the session packet to the mobile node.

12. (Previously Presented) The method of claim 11, wherein the session packet is tunnelled from the correspondent node to the network entity and the network entity decapsulates the session packet prior to forwarding the decapsulated session packet to the mobile node.

13. (Previously Presented) The method of claim 11, wherein the network entity translates the destination address of the session packet to a home address of the mobile node prior to forwarding the session packet to the mobile node.

14. (Currently Amended) A method of operating a network entity at a node of a packet-switched data network, wherein the network entity acts as an intermediate node between a mobile node having a care-of address in a foreign network and a correspondent node, the method comprising: comprising

allocating a secondary care-of address to the network entity, the secondary care of address corresponding uniquely to a home address of the mobile node; and

receiving a packet for the mobile node addressed with the secondary care of address.

15. (Previously Presented) The method of claim 14, further comprising sending a binding update indicating the secondary care-of address to the correspondent node.

16. (Currently Amended) The method of claim 14, including sending a binding update indicating the secondary care-of address to ~~an~~ a home agent (HA) in ~~an~~ a home network (HN) of the mobile node.

17. (Previously Presented) The method of claim 14, further comprising translating the destination address of one or more session packets, received from the correspondent node in a session between the correspondent node and the mobile node, from the secondary care-of address to the home address prior to forwarding the one or more session packets to the mobile node.

18. (Currently Amended) ~~A~~The method according to claim 1, wherein the network entity is located at a gateway to the foreign network.

19. (Currently Amended) The ~~A~~ method according to claim 18, further comprising configuring the network entity as the default gateway of the mobile node.

20. (Currently Amended) The ~~A~~ method according to claim 1, further comprising configuring the network entity as the first hop of the mobile node.

21. (Currently Amended) The ~~A~~ method according to claim 1, wherein the network entity and the mobile node are configured to use MIPv6 protocols.

22. (Currently Amended) A non-transitory computer readable medium comprising instructions which, when executed, cause the method of claim 1 to be performed.

23. (Currently Amended) A non-transitory computer readable medium comprising instructions which, when executed, cause the method of claim 10 to be performed.

24. (Currently Amended) ~~An apparatus arranged~~ A hardware apparatus configured to perform the method of claim 1.

25. (Currently Amended) A non-transitory computer readable medium comprising instructions which, when executed, cause the method of claim 14 to be performed.